

TECHNICAL DATA SHEET

4223 Corehold Tape Double Sided Tape

DESCRIPTION:

4223 Corehold Tape: High adhesion, double coated, natural cloth tape with coated release liner.

APPLICATION:

4223 Corehold Tape: Primary applications include securing honeycomb or other structural core material in place during machining process. Can also be used during pre-fitting of components before final drilling and routing.

TECHNICAL DATA:

TYPICAL VALUES

Backing	Cotton Cloth
Adhesive both sides	Rubber base
Adhesion to steel	50 oz./in. width
Tensile	53 lb./in. width
Thickness	0.011"
Elongation	8.00%
Color	Natural/Tan

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

AVAILABILITY:

Standard available sizes 1/2", 1" or 2" x 36 yards

Other sizes available upon request (minimums may apply)

NOTE: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment.

Technical information furnished is based on laboratory findings and is believed to be correct. No warranties of any kind are made except that the materials are of standard quality. All risk and liabilities arising from handling, storage and use of product, as well as compliance with applicable legal restrictions rest with the buyer. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

