

TECHNICAL DATA SHEET

# 5255 Vacuum Valve

## Three Piece Vacuum Valve Assembly



**DESCRIPTION:**

**5255 Vacuum Valve** is manufactured with an aluminum base plate and lock ring, a steel locking nut and high temperature silicone seal. To prevent bag wrinkling, the lock ring is held in place with a locating pin. Base plate has machined grooves to promote better evacuation.



**APPLICATION:**

5255 Vacuum Valve is designed for through bag vacuum connection in vacuum bag oven or autoclave processing.

**TECHNICAL DATA:**

**TYPICAL VALUES**

Base Diameter	2.75"
Gasket	Silicone
Base Plate & Lock Ring	Aluminum
Locking Nut	Steel
Connection	1/4" MNPT
Maximum use Temperature	500°F (260°C)

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

**AVAILABILITY:**

1/4" NPT standard. Other sizes available on request. Minimums may apply.

Technical information furnished is based on laboratory findings and is believed to be correct. No warranties of any kind are made except that the materials are of standard quality. All risk and liabilities arising from handling, storage and use of product, as well as compliance with applicable legal restrictions rest with the buyer. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.